

Heika-Ground Automatik

Floor access cover system MA-GBZ

Stainless steel-with assisted opening and central closure



Heika-Ground Automatik System GBZ

Product description: The floor access cover system MA-GBZ is made of 2,5 mm stainless steel. The tray depth is 50 mm and the structural height amounts to 75 mm only. The frame is equipped with a circumferential, frost- and weather resistant special sealing joint, which is largely odor- and water-tight. The frame is set in concrete on grade. Subsequently, the tray can be filled and inserted into the frame. The opening process is supported by the high-quality gas pressure springs in a way that the manhole cover can be opened and closed by one single person. The access cover can be opened from the outside and the inside. The tray can be filled with paving, tiles, concrete, artificial resin, granite, terrazzo tiles, wood and hard floor covering or other materials.

Load:
Up 125 kN testing force according to EN 124 (class B125)

Materiel:
Frame and tray made of 2,5 mm stainless steel

Areas of use:
For on grade manholes in indoor or outdoor areas, for which highest quality is required.

Customized:
Customized sizes can be produced in every dimension upon inquiry.

Application options: For manholes which are to be opened quickly and without particular exertion from the outside or the inside. Particularly suitable for underground passages, metro passages, supply shafts of companies or telephone shafts.

Opening: a lifting key and installation instructions are included with every FF floor access cover.

Installation: The installation shall be implemented in a professional manner in accordance with special sealing joint, a tight connection to the frame profile is to be ensured.

Specie benefits of our system:

- Wit frost- and weather-resistant special sealing joint
- with fixing anchors for safe support
- Almost invisible in the installed state
- tray depth amounts to 50 mm
- With additional reinforcement cross-braces
- With gas pressure springs as opening assistance
- Can be opening from the outside and the inside

Item no.	Overall frame size	Clear opening
GBZ600600E75	700x721mm	600x600mm
GBZ800800E75	900x921mm	800x800mm
GBZ10001000E75	1100x1121mm	1000x1000mm

